

# Cool Top Trail 20/24/34

Rooftop air-conditioning systems



Cool Top Trail 20/24



Cool Top Trail 34



Remote Control

## For an ideal climate in your RV

The Cool Top Trail air conditioners are suitable for use in parked motorhomes and caravans of up to 10 m length. With their generously sized heat exchangers they have a high efficiency and high performance. Their reliability and high cooling capacity has already been proven in very hot Australian summers with up to 50°C outside temperatures. The units come with heat pump function as a standard which is also very powerful, working in cold outside temperatures of as low as -5°C.

High performance at low noise Very low noise levels allow you to rest and relax inside the vehicle and not disturb your neighbors in the RV campsite. The use of high-quality components ensures a long lifetime with a minimum expenditure on maintenance.

### Product highlights

- Powerful units with high cooling and heating capacity
- Robust, lightweight and low noise
- Wide operating range from -5 to 50°C
- Low profile and compact design
- Easy installation

Made from UV stabilized polypropylene, the housing of the units is robust but still lightweight. The units can be operated with an easy to handle remote control which allows the user to access all air conditioner functions from the comfort of the dining area, seat or bed. Besides cooling and heating the units include various extra features such as dehumidification, timer and sleep function.

## Technical specifications:

	Cool Top Trail 20	Cool Top Trail 24	Cool Top Trail 34
Cooling capacity (W)	2,000	2,400	3,400
Heating capacity (W)	2,000	2,400	3,000
Nominal voltage/frequency (V)/(Hz)	230~/50		
Rated current (cooling mode)	3	4.2	5.8
Rated current (heating mode)	2.6	3.8	5.4
Operating temperature range (°C)	-5 to 50		
Roof thickness (mm)	25 – 85		25 – 70
Roof cut-out (mm)	400 x 400 (360 x 360 with optional adaptor frame)		
Dimensions outdoor unit (mm)	1,002 x 566 x 215		1,122 x 850 x 223
Dimensions inner unit (mm)	557 x 536 x 43		575 x 515 x 49
Weight total (kg)	30.8	31.8	48